



BILLIARDS:

Baseline Instrumented Lithology Lander, Inspector and Asteroid
Redirection Demonstration System

Matthew Marcus, Joshua Sloane, Oliver Ortiz, Brent Barbee

Department of Aerospace Engineering
The University of Maryland
IAA Planetary Defense Conference
13-17 April 2015



Introduction

▶ BILLIARDS

- ▶ Baseline Instrumented Lithology Lander, Inspector, and Asteroid Redirection Demonstration System
- ▶ Proposed demonstration mission for “Billiard-Ball” concept
- ▶ Select asteroid pair with natural close approach to minimize cost and complexity

▶ Primary Objectives


- ▶ Rendezvous with a small ($<10\text{m}$), near Earth (alpha) asteroid
- ▶ Maneuver the alpha asteroid to a collision with a $\sim 100\text{m}$ (beta) asteroid
- ▶ Produce a detectable deflection or disruption of the beta asteroid

▶ Secondary objectives

- ▶ Contribute knowledge of asteroid composition and characteristics
- ▶ Contribute knowledge of small-body formation
- ▶ Opportunity for international collaboration



Concept of Operations





Alpha Asteroid - 2011 MD

► Physical properties

- Absolute magnitude: 28.0
- Diameter range: 6_{-2}^{+4} m
- Density range: $1.1_{-0.5}^{+0.7}$ g/cm³

► Orbital properties

- Inclination: 2.58°
- Semimajor Axis: 1.06 AU
- Eccentricity: 0.0416
- Orbit classification: Apollo



Beta Asteroid Selection

2010 PR10

24 have a close approach
with 2011 MD after 2024

250 with diameters of
100 to 500 meters

2,000 with OCC = 0

6,500 are not PHAs

11,500 near Earth asteroids

- ▶ Final Beta Asteroid Selection
 - ▶ Collision must occur with radio line of sight to Earth
 - ▶ Must be visible from space based observatories
 - ▶ Ideally visible from ground based observatories
 - ▶ Select minimum close approach distance to alpha asteroid without violating other constraints



Beta Asteroid - 2010 PR₁₀

► Physical properties

- Absolute magnitude: 21.7
- Diameter range: 80-356 m
- Expected diameter: 160 m

► Orbital properties


- Minimum natural close approach: 9.329e-3 AU
- Inclination: 9.2°
- Semimajor Axis: 1.2 AU
- Eccentricity: 0.18
- Orbit classification: Amor

► Close approach

- Five close approaches prior to impact
- Impact date: Jan 26, 2029
- Impact velocity: 6.6 km/s
- Expected Q/Q^* : 9.0
 - Most likely disrupted by impact



Spacecraft Design



- ▶ Instrumentation Module
 - ▶ Houses most spacecraft systems
 - ▶ Provides high Isp propulsion for alpha asteroid rendezvous and redirection
 - ▶ Includes imagers for navigation and scientific data collection
- ▶ Terminal Guidance Module
 - ▶ Houses asteroid capture mechanism and internal sample instruments
 - ▶ Conducts final asteroid guidance maneuvers shortly before collision
 - ▶ High thrust propulsion for autonomous correction maneuvers




Δv Budget

Maneuver Type	Maneuver	Start Date	Δv
<u>Launch</u> Falcon 9 v1.1 Instrumentation Module Terminal Guidance Module	Launch	July 4, 2021	$C_3 = 5.225 \text{ km}^2/\text{s}^2$
<u>Low-thrust</u> Instrumentation Module Terminal Guidance Module	Alpha Rendezvous	July 11, 2021 (L+7d)	1.6 km/s
<u>Low-thrust</u> Instrumentation Module Terminal Guidance Module Alpha Asteroid	Alpha Redirect Midcourse Corrections	August 12, 2025	12 m/s 19.2 m/s
<u>High-thrust</u> Terminal Guidance Module Alpha Asteroid	Terminal Guidance Maneuvers	January 25, 2029 (I-24h)	8 m/s




Terminal Guidance - CONOPS

Alpha asteroid rotating about the position vector between the two asteroids with period T (3 min).



Note: $v_z \gg v_{\text{drift}}$





Spacecraft Mass Estimates

Instrumentation Module


Subsystem	Mass (kg)
Structural	240
Propulsion (dry)	120
SEP Propellant	750
RCS Propellant	50
Power System	401
Thermal	44
Data Processing	61
Attitude Control	64
Science Instrumentation	70
Total Dry	1000
Total	1800

Terminal Guidance Module

Subsystem	Mass (kg)
Structural	240
Propulsion (dry)	26
Bi-propellant	600
Power System	53
Thermal	32
Data Processing	16
Science Instrumentation	70
Capture Mechanism	310
Total Dry	687
Total	1287



FY2014 Cost Estimate



IM P&D Cost	\$518M
TGM P&D Cost	\$334M
Capture Mechanism Cost	\$64M
Launch Vehicle Cost (Falcon 9 v1.1)	\$85M
Total Mission Cost	\$1001M



Conclusion

- ▶ 2011 MD (alpha asteroid)
 - ▶ Density: 1.1 g/cm³
 - ▶ Diameter: 6 m
- ▶ 2010 PR₁₀
 - ▶ Diameter: 160 m
- ▶ Timeline
 - ▶ Earth Departure: July 4, 2021
 - ▶ Rendezvous with Alpha asteroid: July 11 2021 - December 31, 2024
 - ▶ Impact velocity: 6.6 km/s
 - ▶ Collision: January 27, 2029
- ▶ Budget
 - ▶ \$1001M (FY 2014)
- ▶ Mission Objectives
 - ▶ Produce an “artificial” collision between two near-earth asteroids, testing an option for future planetary defense missions
 - ▶ Observe and confirm collision
 - ▶ Gather knowledge of asteroid physical properties
 - ▶ Gather knowledge of asteroid disruption dynamics



References

- ▶ “HORIZONS Web-Interface”, NASA Jet Propulsion Laboratory.
- ▶ “JPL Small-Body Database Browser”, NASA Jet Propulsion Laboratory.
- ▶ Rody Oldenhuis, “Robust Solver For Lamberts Orbital Boundary Value Problem”, January 12 2010.
- ▶ “Dawn Launch Press Kit”, NASA, September 2007.
- ▶ Holsapple, K. A., “Catastrophic Disruptions and Cratering of Solar System Bodies: A Review and New Results, Planetary and Space Sciences”, pp. 1067-078.
- ▶ “Asteroid Retrieval Feasibility Study”, Keck Institute for Space Studies, Pasadena, CA., 2 April 2012.
- ▶ “Deep Impact Launch Press Kit”, NASA, Jan. 2005.
- ▶ Englander, Jacob, et.al., “Evolutionary Mission Trajectory Generator (EMTG)”, Goddard Space Flight Center.



References (cont.)


- ▶ Mommert, M., et.al., “Physical Properties of Near-Earth Asteroid 2011 MD”, 2014.
- ▶ Akin, D. “Principles of Spacecraft Design - Cost Estimation and Engineering Economics”, Space Systems Lab, September 30, 2014.
- ▶ “Near Earth Asteroid Rendezvous - Frequently Asked Questions”, Johns Hopkins University Applied Physics Lab.
- ▶ “Rules for the Design, Development, Verification, and Operation of Flight Systems”, NASA Goddard Space Flight Center, 2/8/2013, Rev. E. pp. 13.
- ▶ “National Space Science Data Center: Stardust/NExT”, NASA.
- ▶ Campbell, J., et.al., “The Impact Imperative: Laser Ablation for Deflecting Asteroids, Meteoroids, and Comets from Impacting the Earth”, Beamed Energy Propulsion: First International Symposium on Beamed Energy Propulsion, Huntsville, AL, November 2002.



Backup Slides




Alpha to Beta Asteroid Multi-Revolution Lambert Solver






Beta Asteroid Distance to Earth





Disruption vs. Deflection



Assumptions

Minimum detectible $\Delta v_\beta = 1 \frac{cm}{s}$

$m_\alpha = 130,000$ kg

$\rho_\beta = 1400 \frac{kg}{m^3}$

Deflection

$$m_\alpha v_{rel} = m_\beta \Delta v_\beta$$

$$r_\beta = \left(\frac{m_\alpha v_{rel}}{\frac{4}{3}\pi \rho_\beta \Delta v_{min}} \right)^{\frac{1}{3}}$$


Disruption

$$Q = \frac{E_\alpha}{m_\beta} = Q_d^*$$

$$r_\beta = \left(\frac{\frac{1}{2}m_\alpha v_{rel}^2}{Q_d^{*4}\pi \rho_\beta} \right)^{\frac{1}{8}}$$




Earth to Alpha Asteroid Trajectory



Designed with EMTG.



Alpha Asteroid Apparent Magnitude





Beta Asteroid Apparent Magnitude

